



DFCE 4000



DFC 2000



A richiesta:

Cassetto interno art. DFC/DATA
per protezione supporti magnetici 60' Data - 60' Dis.

On demand:

Internal drawer art. DFC/DATA
Data Protection 60' Data - 60' Dis.

Serratura a Cilindro o Combinazione Elettronica

- Protezione contro il fuoco di 60 min. in condizioni di esposizione al fuoco ad una temperatura di 1010°C.
- Struttura monoblocco.
- Dotazione di 2 o 4 cassetti, secondo il modello, scorrevoli su robuste guide.
- Cassetti isolati singolarmente.
- Supporti per cartelle sospese.
- Sistema di sblocco interno ad ogni singolo cassetto per renderlo indipendente dalla serratura centrale.
- I classificatori sono dotati di ruote e profili copriruote.

• **Art. DFC:**
Serratura a cilindro

• **Art. DFCE:**
Serratura elettronica digitale



Cylinder Lock or Digital Electronic Combination

- Fire protection of 60 min. at a constant temperature of 1010°C.
- One-piece steel body.
- 2 or 4 drawers with heavy duty suspension slide rails to make the drawer move back and forth smoothly.
- Adjustable supports for hanging folders.
- Each drawer is isolated from the others.
- Each drawer has a special hook inside with lock and unlock position.
- Equipped with wheels and metal wheels covers.

• **Art. DFC:**
Cylinder lock.

• **Art. DFCE:**
Digital electronic lock.

Art	Misure esterne mm.			Misure interne mm.			Resistenza al fuoco	Cassetti	Peso	Litri	
Code	External dim. mm.			Internal dim. mm.			Fire Resistance	Drawers	Weight	Volume	
	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W	Prof/D	Minuti/Min	N°	Kg	Lt	
DFC 2000	820	528	675	254	384	505	60	2	145	99	
DFC 4000	1500	528	675	254	384	505	60	4	266	197	
DFCE 2000	820	528	675	254	384	505	60	2	145	99	
DFCE 4000	1500	528	675	254	384	505	60	4	266	197	
Optional DFC/DATA	-	-	-	162	282	402	60 - data / dis	-	20	18	