



GMT/5

- Frontale e Porta 10 mm
- Corpo 5 mm
- Taglio Laser
- Front and Door 10 mm
- Body 5 mm
- Laser Cut



CERTIFICATA A NORMA EUROPEA
UNI EN 14450-S1
CERTIFIED TO EUROPEAN STANDARD
EN 14450-S1



Digital Electronic Combination

- Digital electronic lock EN 1300 certified, controlled by a high performing electronic system provided by permanent memory.
- Opening/closing with recessed knob and locking by electromagnet.
- Internal power with alkaline battery (not included).
- High quality membrane keyboard with 4 leds.
- Acoustic and visual signals to confirm codes, errors and internal battery deficiency.
- Emergency external power outlet with contacts directly on keyboard.
- Nickel-plated rotating steel bolts $\varnothing$ 22 mm (GMT/3 $\varnothing$ 18mm, fixed).
- Lock mechanism protected by a manganese-steel plate.
- Horizontal and top vertical bolts protected by drill resistant manganese-steel plate 3 mm thick, placed askew in order to get the best resistance to drilling.
- Special door battens for exceptional resistance against robbery attempts using a sledge hammer.
- Internally welded by a robot-controlled system.
- Front panel seam-welded to the casing by a robot-controlled system.
- Removable internal shelf.
- Base and back fixing holes.
- Screw anchor fixing bolts provided.
- Oven dried thermo-hardening powder painting.

Art	Misure esterne mm.			Misure interne mm.			Dim. porta mm.		Numero catenacci		Peso	Litri	
Code	External dim. mm.			Internal dim. mm.			Door dim. mm.		Number of bolts		Weight	Volume	
	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W	Oriz/Horiz	Vert	Kg	Lt	
GMT/3	220	350	300	200	340	245	140	250	2	-	25	18	
GMT/4	280	400	350	260	390	295	195	300	2	1+1	35,5	31	
GMT/5	350	470	350	330	460	295	265	370	3	1+1	47,5	47	
GMT/6	430	490	350	410	480	295	345	390	3	2+2	56	60	
GMT/7	490	430	400	470	420	345	405	330	3	2+2	61	70	

A richiesta, tutti i modelli elettronici possono essere dotati di serratura per un'apertura meccanica di emergenza con chiave di alta sicurezza a doppia mappa (EVO-LOCK). Il modello con chiave di emergenza GMT/3P non è certificato UNI EN 14450.

Codice prodotto di questa serie: aggiungere la lettera "P" alla fine del codice del prodotto standard.

Esempio: GMT/3 senza chiave di emergenza diviene GMT/3P con chiave di emergenza, GMT/4 diviene GMT/4P, etc.

On demand, the electronic models, can be equipped with a mechanical emergency opening with double-bitted key lock (EVO-LOCK). The model with emergency key GMT/3P is not EN 14450 certified.

Code for this series: add a "P" at the end of the code.

Ex. GMT/4 for a safe without emergency lock becomes GMT/4P for a safe with emergency lock, GMT/5 becomes GMT/5P, etc.

Serratura di emergenza con chiave a doppia mappa. Emergency lock with double-bitted key (Mod. 3).

Serratura di emergenza con chiave a doppia mappa. Emergency lock with double-bitted key (Mod. 4-5-6-7).