



070 SDBK

Chiave a Doppia Mappa

- Alta protezione contro il fuoco: resistenza da 60 a 90 min. secondo il modello in condizioni di esposizione al fuoco ad una temperatura di 1010°C.
- Serratura ad alta sicurezza testata EN 1300 con chiave femmina a doppia mappa.
- Cassa interna supplementare costituita da pannelli di materiale melaminico e da specifiche protezioni che hanno funzione di isolante termico.
- Le guarnizioni della cassa interna e le scanalature della porta esterna assicurano la tenuta ermetica a liquidi, aria, vapore e fumo.
- Protezione contro i campi magnetici ed i fenomeni elettrostatici.
- Piedini in gomma alla base.

Double-Bitted Key

- High fire protection: from 60 min. up to 90 min. fire resistance, depending on the model, at a constant temperature of 1010°C.
- Lock controlled by a high security lock with double-bitted key, EN 1300 certified.
- Additional internal box, made of melamine panels and heat insulating materials.
- The gaskets on the internal box and the grooves on the external door ensure a hermetic seal against liquids, air, gas, steam and smoke.
- Protection against magnetic fields and electrostatic phenomena.
- Equipment with rubber support feet on the bottom.



Art	Misure esterne mm.			Misure interne mm.			Resistenza al fuoco	Ripiani	Peso	Litri	
Code	External dim. mm.			Internal dim. mm.			Fire Resistance	Shelves	Weight	Volume	
	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W	Prof/D	Minuti/Min	N°	Kg	Lt	
125 SDBK	420	352	433	224	157	206	60 - data/dis	1	43	7	
530 SDBK	522	404	440	314	197	201	60 - data/dis	1	65	12	
070 SDBK	695	500	500	419	277	231	90 - data/dis	1	117	27	

Art	Capacità interna						
Code	Internal Capacity						
	4mm DAT	8mm AIT	CD	DLT	LTO/Ultrium	LTO/Ultrium (without case)	3590 Cartridge (without case)
125 SDBK	74	33	30	16	-	22	12
530 SDBK	150	54	53	20	-	36	22
070 SDBK	312	168	111	62	-	96	64