GOLD Key-PT

CASSEFORTI A MURO
WALL SAFES



GK/4-PT



Chiave doppia mappa
Con DEFENDER PRO-TECH brevettato

- **PRO-TECH è un CONGEGNO INNOVATIVO ROTANTE per la PROTEZIONE TOTALE dell'ENTRATA della CHIAVE**
- **Realizzato completamente in acciaio inox per contrastare tentativi di attacco con grimaldello, scalpello, trapano e acido.**
- **RUOTANDO blocca o sblocca l'ingresso della chiave.**
- **CHIAVE a DUPLICAZIONE PROTETTA con SERCURITY CARD.**
- **La sua funzione è quella di creare una barriera aggiuntiva contro i tentativi di manipolazione, perforazione, impedendo qualsiasi manomissione o forzatura diretta dell'ingresso chiave.**
- Serratura di alta sicurezza di ultima generazione con 8 leve assimmetriche ed indipendenti, certificata EN 1300.
- Chiave a doppia mappa con profilo speciale dupplcabile con carta di proprietà per impedire la duplicazione non autorizzata della chiave.
- Chiave inestraibile a porta aperta (catenacci rientrati).
- Catenacci girevoli in acciaio nichelato Ø 22mm.
- Protezione al meccanismo della serratura con piastrina di acciaio al manganese.
- Speciali battute della porta per resistere più a lungo ai tentativi di effrazione con mazza.
- Ripiano interno.
- Verniciatura con polveri termoindurenti.



- Frontale e Porta 10 mm
- Taglio Laser

Double-bitted key
With patented PRO-TECH DEFENDER

- ***PRO-TECH is an INNOVATIVE ROTATING DEVICE for TOTAL PROTECTION of the KEY ENTRY.***
- ***Made entirely of stainless steel to resist attack attempts with lockpicks, drills, chisel and acid.***
- ***By rotating, it blocks or unlocks the key entry.***
- ***PROTECTED KEY DUPLICATION with SECURITY CARD.***
- ***Its function is to create an additional barrier against manipulation, drilling attempts, preventing any tampering or direct forcing of the key entry.***
- *Latest generation high security lock, EN 1300 certified, with 8 asymmetrical and independent levers.*
- *Double-bitted key with special profile, duplicable with the ownership card to prevent unauthorized key duplication.*
- *Key-retaining lock in open position.*
- *Nickel-plated rotating steel bolts Ø 22mm.*
- *Lock mechanism protected by a manganese-steel plate*
- *Special door battens for exceptional resistance against robbery attempts using a sledge hammer.*
- *Internal shelf*
- *Oven dried thermos-hardening powder coating.*

- *Frame and Door 10 mm*
- *Laser Cut*

CERTIFICATA A NORMA EUROPEA UNI EN 14450:18-S2
CERTIFIED TO EUROPEAN STANDARD EN 14450:18-S2

LASER CUT TAGLIO LASER
MORE RESISTANCE MAGGIOR RESISTENZA

EVO-LOCK

Art.	Dim. esterne mm.			Dim. interne mm.			Dim. porta mm.		Numero catenacci		Peso	Litri
Code	External dim. mm.			Internal dim. mm.			Door dim. mm.		Number of bolts		Weight	Volume
	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W	Oriz/Horiz	Vert	Kg	Lt
GK/4-PT	270	390	200	245	365	150	195	300	2	1+1	18	14
GK/5-PT	340	460	200	315	435	150	265	370	3	1+1	25	21
GK/7-PT	480	420	280	455	395	230	405	330	3	2+2	34,5	43